


BLU BAT 52-67-79

The solid floorboards are nailed to a resilient subconstruction of one layer engineered battens including a continuous layer of 9 mm thick sports foam pre-mounted on the underside of the

There is a choice of 3 batten thicknesses, 30mm 45mm or 57mm.

FACTS:			
Performance	Area-elastic according to EN 14904 class A3		
Use	Small sports halls/dance/fitness/squash Refurbishment Low impact sport		
Floorboard type	Prefinished 22mm 2-strip solid hardwood parquet		
Subconstruction	Single layer batten system		
Batten centre c/c	Choice between 336mm and 411mm		
Required subfloor	Even		
Construction height	Choice between 52mm, 67mm, 79mm		
Sanding and re-sealing	Yes 8-10 times		
Suitable for underfloor heating	Yes		



SYSTEM COMPONENTS

- 1. 22 x 129 x 3700mm floorboards
- 2. BluBAT batten system including sportsfoam
- 3. Polythene moisture barrier
- 4. Combi sports skirting

TEST:	Requirements EN 14904:A3	Test ro 411mm Batten	
Shock absorption	≥ 40 < 55 %	55%	53%
Wertical deformation	≥1.8 < 3.5mm	1.9mm	1.8mm
Ball bounce	<u>≥</u> 90 %	100%	98%
Friction	≥80≤110	100	100
Rolling load	≥1500 N	✓	1
_		3000 N1)	3500 N1)
Point load	None	5000 N ~ 500 kgs ²)	5500 N ~ 550 kgs ²)

 $^{^{1)}}$ Junckers' test with solid rubber wheels, width = 50mm, diameter = 100mm. $^{2)}$ Junckers' test with 100x100mm point load.